



Visit our new Lipa
Facebook group at
Lipa Mowers And Mulchers



Please click the QR code to the left, or enter "Needham Lipa TLBE-SF" into YouTube to see a video of the Lipa TLBE-SF flail mulcher in action!

TLBE-SF

Flail Mulchers For 10,000 - 16,000 lb Mini Excavators

No Case Drain Required



Optional hydraulic hoses are available from Needham Ag

The Lipa TLBE-SF series of flail mulchers are designed to bridge the gap between the TLBE-S flail mowers and the TLBE-FS mulchers, both from a cost and performance perspective. They feature swinging hammers, which are reversible, in addition to heavy safety chains across the front and rear, to help control flying debris. Heavy duty skid plates are present on both ends to help control cut height. This mower is designed to mulch up to around 4-5" materials, but it can process larger trees with slow and careful operation (see video link above).

The TLBE-SF series flail mulchers also feature a manual adjust front door, which in the raised position allows you to cut the top off small trees from the side, then mulch them to the ground. With the door lowered, the chains almost eliminate the material thrown (which is very important when operating around homes or roads).



Model	Overall Width (inches)	Cutting Width (inches)	Weight (lb) *	Rotor Speed (RPM)	Required Oil Flow (gal/min)	Ideal Oil Pressure (PSI)	Number Of Flails	Number Of Drive Belts	Price \$
TLBE-SF 70	37	27	760	2300	17-23	3500	11	3	8990
TLBE-SF 90	46	35	800	2300	20-24	3500	15	3	9490
TLBE-SF 110	53	43	840	2300	20-24	3500	18	3	9990

* Approximate weight, with typical mounting bracket and optional hydraulic hoses.

Options

Hydraulically Adjustable Front Door.

Standard Equipment

- Excavator hookup linkage for most mini excavators, but some will require a specialist mount (which will incur an additional charge). Mounting pins are not included in the prices above.
- Electronically balanced, heavy duty 6 1/2" diameter rotor, with scrolled reversible hammers.
- Heavy duty lateral skids.
- Chains across the front and rear, to help control flying debris.



The standard option on the TLBE-SF flail mulcher is a manual adjust front door. This model has a linkage (with a pin) to secure the door position.

If you have a mini excavator with a 2nd pair of auxiliary lines, then you can order the TLBE-SF mower with a hydraulic cylinder. This option allows you to raise and lower the front door, like you would the thumb. This allows you to cut the top out of trees, then lower the front door to control flying debris. Note: Hydraulic hoses are not included, but are they are available for an additional cost.

290