



TLS

Heavy Duty Flail Mower (With Side-Shift Feature)

For 30 - 100 hp Tractors*



Mulching teeth are available as an option to order

These mowers are also available without the side-shift feature.

The TLS Flail Mower is perfect for mowing and shredding dense grass, brush and small trees up to around 3" in diameter. They cut/mulch finer than rotary cutters and provide a more even finish. This mower also features a heavy duty rear roller and has optional side skids.

This TLS model has a hydraulic side shift feature which provides 16" of total side to side travel (8" either way of center). This side shift feature makes mowing around trees, fences or other objects much easier, especially within orchards or tree farms.

TLS mowers are also available with the steel mulching teeth for greater mulching.

Model	Overall Width (inches)	Cutting Width (inches)	Weight (lb)	PTO Speed (RPM)	Required Tractor HP*	# Of Flails	# Of Drive Belts	Price \$
TLS 140	61	57	1120	540	30-50	10	3	6290
TLS 150	70	65	1210	540	40-60	11	4	6590
TLS 180	77	72	1330	540	50-70	12	4	7090
TLS 200	84	79	1380	540	60-80	13	4	7490
TLC 220	93	88	1440	540	70-100	15	4	7990

* The higher end of the horsepower range is recommended if cutting taller/thicker grass or denser brush.

Standard Equipment

- Three Point Linkage (With Pins), PTO Shaft (With Heavy Shield).
- Heavy Duty Gearbox (With Free Wheel Feature).
- Front Rubber Flap & Safety Chains To Help Control Flying Debris.
- Electronically Balanced, Heavy Duty Rotor, With Heavy Duty Tri-Tooth Flails and Heavy Duty Flail Hangers.
- Internal Steel Counter-Blades To Help With Mulching.
- Heavy Duty Adjustable Steel Roller, With Scraper.
- Opening Rear Shield To Let Heavy Material Discharge.
- Hydraulic Hoses (To Operate Side Shift Frame).

Options

Lateral Skids

If the mower is to be used for long distances, especially on undulating ground, we recommend the lateral skids on both ends. This reduces the wear on ends of the mower frame (under most conditions the mower weight will be on the rear roller).



310